Product data sheet Characteristics

SRT192RMBP

APC Smart-UPS SRT 192V 5kVA and 6kVA RM **Battery Pack**





$\overline{}$						
()	W	Ω	r۱	/16	21	٨/

Lead time	Usually in Stock
Leau time	Ostally III Stock

General

Provided equipment	Installation guide
	Warranty card

Physical

		u c
		i de la companya de l
		ğ
		ي ا
Overview		
Lead time	Usually in Stock	
		<u> </u>
General		
Provided equipment	Installation guide	
	Warranty card	Alice Control of the
		<u>a</u>
Physical		the state of the s
Colour	Black	
Depth	68.27 cm	
Height	13 cm	
Net weight	91 kg	
Number of rack unit	3U	
Width	43.2 cm	
Conformance		<u>y.</u> 2
Standards	OSHPD	
		Stiff
Environmental		
Ambient air temperature for operation	040 °C	<u>ر</u> 0
Ambient all temperature for operation	040 0	40

Conformance

Standards	OSHPD

Environmental

		(0
Ambient air temperature for operation	040 °C	papu
Operating altitude	010000 ft	inter
Relative humidity	095 % non-condensing	is not
Ambient air temperature for storage	-1545 °C	ation
Storage altitude	0.0015240.00 m	nenta

Batteries & Runtime

Number of battery free slots	0		

Number of battery filled slots	0
Device mounting	Stand alone battery stack
Battery voltage	192 V
Battery type	Lead-acid battery
Number of battery replacement quantity	2

Packing Units

Package 1 Weight	105.5 kg
Package 1 Height	42 cm
Package 1 width	60 cm
Package 1 Length	100 cm
Number of Units in Package 3	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------